



ASSEMBLY INSTRUCTIONS

1. Carefully unpack and identify all parts referring to illustration for parts identification.
2. Turn the power to the installation point OFF.
3. Remove the finial (H) from the nipple (D). Place the long end of the amber glass (F) facing up on the ring to the left of the fixture body (A) and the long end of the smoked glass (E) facing up on the ring to the right of the fixture body (A). Confirm that the holes on the amber glass (F) and smoked glass (E) align with the holes on the ring of the fixture body (A). Pass the nipple (D) through holes of the fixture body (A), amber glass (F) and smoked glass (E), secure with finial (H). Hand-tighten until snug.
4. Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
5. Remove the lock screws (C) from the ring. Place the clear glass (G) to the top on the fixture body (A), place the clear glass (B) to the bottom on the fixture body (A). Confirm that the holes on the clear glass (G) and clear glass (B) align with the mounting holes on the fixture body (A). Pass the lock screws (C) through mounting holes on the fixture body (A), the holes on the amber glass (H) and the smoked glass (E). Hand-tighten until snug.
6. Refer to the additional installation instructions included with the product for wiring and installation.
7. Restore power to the installation point and retain this sheet for future reference.